

Steam iron

Oven

Washing machine

Dish washer

Refrigerator

Coffee pot

Microwave oven

Electric razor

Vacuum cleaner

Drills

Saws

Dow Corning® and Molykote® Solutions for Home Appliances



DOW CORNING

Sealants & Lubricants for the Home Appliance Market

When it comes to providing safety, reliability, durability and compatibility for the home appliance market, designers and engineers around the world turn to Dow Corning for sealant and lubricant solutions.

Innovative technology is designed into every one of our products—from our *Dow Corning*® brand of sealants and gaskets to our *Molykote*® brand lubricants, greases and anti-friction coatings. Every product is backed by our commitment to provide design and processing answers when you need them.

Our functionality testing, application engineering, and equipment/material integration provide you with a total systems solution. Our product range and engineering expertise make us the ideal partner for cooperation and development of projects for modified or new products.

- **Tailored approach** – Dow Corning has global capabilities but can tailor a solution that can satisfy local needs.
- **Environmentally friendly** – Our silicone-based products and lubricants do not contain heavy metals or unwanted chemicals.
- **Total solution** – We offer a wide selection of sealants and specialty lubricants for all applications to help you make the right choice the first time.

As the global leader in silicon-based technology and with more than 60 years of experience as a silicone supplier, Dow Corning provides products, services and business solutions to meet your needs exactly. Whether you need to boost performance, lower costs, or increase customer satisfaction with your systems, modules and components, we have experts who can help.

When you select Dow Corning as your business partner, you get fully integrated application and engineering support along with high-quality products and materials. From parts manufacturing to consulting to critical components' design, our experts can customize solutions that provide safety, reliability and durability for the home appliance market.

This guide will assist you in selecting the best sealant or lubricant for your specific application needs. Technical data sheets are available for all products.



AV10080



AV10086



AV10089



MOLYKOTE
FROM DOW CORNING

Smart Lubrication™

Sealants

Regardless of how harsh the environment or how extreme the temperature, we are sure to have a *Dow Corning®* sealant to meet your needs.

Dow Corning sealants are formulated using a variety of product technologies, each providing strengths and characteristics unique to its chemistry.

Silicon-based Dow Corning sealants last longer and are more versatile than most organic polymer sealants. Our products offer exceptional performance characteristics and meet a wide variety of your industrial bonding and sealing needs.

Selecting the right product can help you lower costs by improving performance. Our technical experts can help you choose the right Dow Corning solution to enhance the value of your product.

Let us know which product features are most important to your application. We can tailor our products and services according to your specific requirements.

Features of Dow Corning silicone sealants include:

- **Stability over a wide temperature range** – When fully cured, our products can be used at temperatures ranging from -85° to 599° F (-65° to 315° C).
- **Weather resistance** – High resistance to UV rays, radiation and weather prevents from hardening, cracking, crumbling, drying and becoming brittle.
- **Chemical stability** – Our sealants do not readily degrade even under long-term exposure to many chemicals and atmospheric pollutants.
- **Good bond strength** – Our products provide good adhesion to a wide variety of industrial materials,

Sealant Applications



Application

Part

Recommended Dow Corning® products

Steam iron

- Steam chamber adhesive, seal
- Sole plate adhesive, seal

3-6006, 736, Q3-3379, 3-6458

Oven

- Door window adhesive, seal

3-6045, 3-6096, Q3-3526

Washing machine

- Tub seal
- Water pump seal
- Water distributor seal

7091, 3-8159RF

Dishwasher

- Steam generator seal
- Water pump seal

Q3-3379, 8888

Ceramic hob

- Frame to kitchen desk foam seal
- Glass to frame adhesive, seal

3-8119RF, 732, 832, Q3-1566, Q3-3526

Refrigerator

- Plastic/plastic, plastic/metal seam seal
- Silicone rubber gasket adhesive

732, 737, 832, 7091

Coffee pot

- Plastic handle to glass adhesive
- Heating plate seal
- Seal for electrical parts

9-1363, 1537

Microwave oven

- Door window adhesive, seal

732, 736, Dow Corning Toray SE 9592HT

Recommended products are Dow Corning® brand unless otherwise noted. Product availability may vary by region, so please check with your local Dow Corning contact.

Lubricants

including glass, ceramics, and wood masonry, painted surfaces, and many metals and plastics.

- **Electrical properties** – Designed for a variety of applications, our products can be used in various electrical and electronic applications, including devices that are thermally cycled over a wide temperature range.
- **Low Flammability** – In fire conditions, silicone adhesives/sealants resist burning. Many products comply with UL flammability standards.

When you specify an assembly and maintenance product from Dow Corning, you receive a solution backed by the world leader in silicone technology with more than 60 years of expertise and innovations.

Performance requirements

- Resistance against heat, hot water, and water vapor
- Good adhesion to aluminum, die cast aluminum and stainless steel

- Resistance against heat (up to 250oC),
- Good adhesion to glass, enamel, painted metal and stainless steel

- Good adhesion to metals and engineering plastics
- Resistance against water and detergent
- Anti-shake resistance

- Good adhesion
- Resistant to water and high temperature

- Heat and hot water resistance

- Good adhesion to plastics, metals, and silicone rubber
- Good adhesion/flexible bond at low temperatures

- High green strength, good adhesion
- Heat resistance
- Detergent resistance

- Heat resistance
- Good adhesion to glass and painted metal

When you select Dow Corning as your preferred lubricant supplier, you get access to our extensive offering of *Molykote*[®] brand lubricants, specialty greases, pastes, anti-friction coatings, oils and dispersions, as well as unmatched application expertise.

Molykote lubricants can be used in situations requiring high pressure or in extreme temperatures, where you have vibration and shock loads, or between sliding surfaces operating under heavy loading. Also, many of our lubricants are food-grade certified.

Molykote lubricants are designed to perform optimally on a variety of substrates, including metals, elastomers and engineered polymers. Regardless of the scope and scale of lubrication support you require, we can provide the exact combination of products and services that you need to succeed.

Simply put, the right lubricant for a moving part can mean the difference between high performance and failure.

Lubricant Applications



Application

Oven

Electric shaver

Vacuum cleaner

Other

Cordless drill

Reciprocating saw

Hobby drill



The Molykote line of specialty lubricants for appliance components includes:

- **Greases** – Thick or semi-fluid dispersions of a thickening agent in a lubricating liquid. High-performance greases are designed for dynamic metal-to-metal, metal-to-rubber, metal-to-plastic and plastic-to-plastic applications. Most greases are based on synthetic formulations that have excellent resistance to thermal degradation. Many are fortified with solid lubricant additive technology to provide effective lubrication under extreme load conditions. High-performance fluorinated greases are designed for extended service at higher temperatures and higher loads, and in harsh chemical environments.
- **Pastes** – High concentrations of solid lubricants dispersed in oil for convenient application. These lubricants have high concentrations of solid lubricants blended in various bases. They are used

where a high concentration of solid lubricant is required, such as initial run-in and areas exposed to high loads.

- **Anti-friction coatings** – Paint-like products that contain submicron-sized particles of solid lubricants instead of coloring pigment, dispersed through carefully selected resin blends and solvents. After curing, the coating forms a dry lubricating film that can help prevent corrosion and is aesthetically pleasing. Anti-friction coatings are ideal for applications involving dusty environments or for inaccessible areas containing parts that need long-term lubrication.
- **Semi-dry lubricant** – Clear, color dispersions that contain fluorinated solid lubricants and slight amounts of fluorinated oil mixed into non-flammable solvent. These lubricants dry quickly after a thin layer is applied.

Part	Recommended Molykote® products	Performance requirements
Bearing and gear lubrication	HP-500	High temperature resistance
Door hinge	D-708	Noise cancelling, heat resistance, good aesthetics
Blade lubrication and protection	557	Dry film
Plastic joint lubrication	PD-910	Plastic compatibility, clean lubricant
Switch spring lubrication	G-5032, 316 spray	High temperature resistance (170°C), water resistance
Refrigerator plastic shelves and trays lubrication	Dow Corning® 7 EM-50L	Low temperature resistance Good feel
Bearing lubrication in food machines	G-0052, G-4500	Food grade, high speed
Bearing and gear lubrication	G-68	Plastic compatibility, white
Bearing and gear lubrication	G-0010	Long life grease, extreme pressure lubrication, shear resistant
Bearing and gear lubrication	G-0010	Long life grease, extreme pressure lubrication, shear resistant

Recommended products are Molykote® brand unless otherwise noted. Product availability may vary by region, so please check with your local Dow Corning contact.

How To Contact Us

Dow Corning has sales offices, manufacturing sites, as well as science and technology laboratories around the globe. For more information, visit www.dowcorning.com or www.molykote.com, or call one of our primary locations listed here.

Your Global Connection

The Americas

World Headquarters (United States)
Telephone: + 1 989 496 6000

Automotive Development Center N. America
Telephone: + 1 734 454 2000

Brazil

Dow Corning do Brasil Ltda.
Telephone: + 55 11 3759 4300

Asia

Asia Headquarters (Japan)
TEL: + 81 3 3287 8300
FAX: + 81 3 3287 1088

China

TEL: + 86 21 2306 5500
FAX: + 86 21 6351 2600

India

TEL: + 91 22 6694 6868
FAX: + 91 22 6694 6848

Korea

TEL: + 82 2 551 7600
FAX: + 82 2 551 6400

Singapore

TEL: + 65 6253 6611
FAX: + 65 6253 6070

Australia & New Zealand

Dow Corning Australia Pty Ltd.
Telephone: + 61 1300 360 732

Europe

European Headquarters (Belgium)
Dow Corning S.A.
Telephone: + 32 64 88 80 00

Germany

Dow Corning GmbH
Automotive Center Europe
Telephone: + 49 611 23 70

France

Dow Corning France S.A.
Sales Office
Telephone: + 33 47 284 1360

Italy

Dow Corning S.p.A.
Sales Office
Telephone: + 39 0298 8321

Spain

Dow Corning Iberica
Sales Office
Telephone: + 34 93 363 6900

United Kingdom

Customer Service Center Northern Europe
Sales Office
Telephone: + 44 1676 528 000

Global Presence. Local Support.

Dow Corning's global presence enables you to develop specifications centrally while providing consistent high-quality products and services locally. Through our global sales, application engineering, product development and manufacturing and delivery capabilities, our quality is consistent around the globe. This also enables a more effective and efficient product customization process—no matter where you are located!

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that Dow Corning's products are safe, effective, and fully satisfactory for the intended use. Suggestions of uses should not be taken as inducements to infringe any particular patent.

Dow Corning's sole warranty is that the product will meet the Dow Corning sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Dow Corning is a registered trademark of Dow Corning Corporation.

Molykote is a registered trademark of Dow Corning Corporation.

We help you invent the future is a trademark of Dow Corning Corporation.

© 2006 Dow Corning Corporation. All rights reserved.

Form No: 80-3334-01

Cover images: AV10085, AV10087, AV10088, AV05469

*We help you
invent the future.™*

DOW CORNING

www.dowcorning.com