

# STATICIDE ACRYLIC FLOOR FINISH

Product Code: E40001AF / E40005AF

## PRODUCT DESCRIPTION

**Staticide Acrylic** is a high performance, low cost method of protecting sensitive manufacturing areas from the dangers of static build up.

## PRODUCT USE

Perfect for production areas, warehousing, shipping, laboratories and electronic repair facilities.

## FEATURES

- \* Easy to apply
- \* Cost effective in use
- \* Protects against damage caused by static discharge
- \* Leaves a shine
- \* Non-flammable

## TOXICITY AND MATERIAL SAFETY

In ready to use form, this product is non-toxic and non-flammable.

## TYPICAL PROPERTIES

Density:	1.0
Boiling Point:	100°C
Solubility in Water	100
Odour:	Ammonia
pH:	8.0
% Volatile:	80
Physical State:	Liquid
Appearance:	Opaque, white liquid

TECHNICAL  
DATA  
SHEET



**Copyright  
Electrolube  
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



## STATICIDE ACRYLIC FLOOR FINISH – Page 2

### DIRECTIONS FOR USE

Clean floor thoroughly to remove old material with stripper. Neutralise the floor with Anti-static Neutraliser Cleaner. Using a clean rayon string mop, apply 3 thin coats of **Acrylic Static Floor Finish** waiting 1 hour (minimum) between each coat.

Note: High humidity levels will require a longer drying time.

Note: To eliminate static, coated floor must be in contact with an electrode ground.

### PACKAGING

1 Gallon (US) (3.75 Litres)  
5 Gallons (US) (18.75 Litres)

### ORDER CODE

E40001AF  
E40005AF



This product is distributed on behalf of ACL Staticide, 1960 East Devon Avenue, EIK Grove Village, IL 60007 USA. An ISO9002 certified company.

Tel: 847 981 9212 Fax: 847 981 9278 Website: [www.aclstaticide.com](http://www.aclstaticide.com)

### TECHNICAL DATA SHEET



### Copyright Electrolube 2003

All information is given in good faith but without warranty.

Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

