

# STATICIDE ANTI-STATIC FLOOR STRIPPER

Product Code: E40101FS

## PRODUCT DESCRIPTION

**Staticide Anti-Static Floor Stripper** removes embedded dirt providing a completely clean and finish-ready surface by emulsifying dirt and residual particles of old wax or coating.

## PRODUCT USE

Removes multiple coats of wax or synthetic floor finishes.

## FEATURES

- \* Will not damage or dull flooring when used according to manufacturer's recommendations
- \* Non-ammoniated
- \* Biodegradable
- \* No harsh odours
- \* Non-streaking
- \* Low foaming
- \* Effective in hard or soft water
- \* Dilution ratio-1:16 (1 part stripper to 16 parts water)

## TOXICITY AND MATERIAL SAFETY

### **WARNING:**

Not to be taken internally. Avoid inhaling fumes or direct exposure to eyes or skin. Wear eye and skin protection during mixing and use.

### **FIRST AID:**

**Eyes:** Flush with liberal amounts of water and seek medical advice immediately.

**Skin:** Flush with liberal amounts of water.

**Oral Ingestion:** Take copious amounts of water and fruit juice – seek medical advice immediately.

**IF UNCONSCIOUS** treat for shock, administer oxygen and transport immediately to an emergency facility.

TECHNICAL  
DATA  
SHEET



**Copyright  
Electrolube  
2003**

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification. Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.



# STATICIDE ANTI-STATIC FLOOR STRIPPER

– Page 2

## TYPICAL PROPERTIES

Boiling Point:	100C/212F
Solubility in Water:	100
Odour :	Slight solvent
pH:	10.9-11.9
Physical State:	Liquid
Appearance:	Red

## DIRECTIONS FOR USE

1. Sweep floor to remove surface dirt and debris.
2. Dilute 1 part stripper to 16 parts water.
3. Apply dilution to floor and re-apply as required to keep floor wet for 10-15 minutes.
4. Scrub floor with abrasive pad to loosen all old finish and dirt.
5. Rinse floor thoroughly with water.
6. Pick up with wet vacuum or mop.
7. Repeat as necessary to completely flush stripper. Residual stripper will affect the performance of the final floor finish.
8. Floor must be completely dry before applying floor finish.

## PACKAGING

1 Gallon (US) (3.75 Litres)

## ORDER CODE

E40101FS

**ACL Staticide**<sup>®</sup>

This product is distributed on behalf of ACL Staticide, 1960 East Devon Avenue, EIK Grove Village, IL 60007 USA. An ISO9002 certified company.

Tel: 847 981 9212 Fax: 847 981 9278 Website: [www.aclstaticide.com](http://www.aclstaticide.com)

## TECHNICAL DATA SHEET



## Copyright Electrolube 2003

All information is given in good faith but without warranty.

Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

