

MDS Metal Degreasing Solvent

MDS is a special solvent for the most critical electro-mechanical applications. MDS is highly recommended for cold cleaning applications in conjunction with all types of electro-mechanical equipment. MDS contains Dichloromethane; please refer to the MSDS before use.

- Powerful, penetrating action, works faster and more thoroughly than conventional solvents
- Non-flammable, eliminates the risk of fire caused by flammable solvents
- Non-conductive, therefore safe to use on electrical equipment
- Fast drying and leaves no residue; suitable for use where water-based cleaning is inadvisable

Typical Properties

Form:	Clear, Colourless Liquid
Boiling Point:	40°C
Vapour Pressure @ 20°C:	355 mm/Hg
Density (g/ml @ 20°C):	1.32
Decomposition Temperature:	>200°C

<u>Description</u>	<u>Packaging</u>	<u>Order Code</u>	<u>Shelf Life</u>
Metal Degreasing Solvent	1 Litre Bulk	MDS01L	36 Months

Directions for Use

Note 1: MDS is harmless to metals under normal conditions. However, it affects certain thermoplastics and fabrics and a small area must be tested before use.

Note 2: In common with other halogenated solvents, MDS should not be used for prolonged periods (e.g. overnight) in contact with aluminium or in circumstances under which the protective oxide film is removed.

Revision 1: Apr 2014

Copyright Electrolube 2013

All information is given in good faith but without warranty. Properties are given as a guide only and should not be taken as a specification.

Electrolube cannot be held responsible for the performance of its products within any application determined by the customer, who must satisfy themselves as to the suitability of the product.

Ashby Park, Coalfield Way,
Ashby de la Zouch,
Leicestershire LE65 1JR
T +44 (0)1530 419 600
F +44 (0)1530 416 640
BS EN ISO 9001:2008
Certificate No. FM 32082