



D-5015NS / ZC-015 Bulk

DESCRIPTION

D-5015 NS is a light lubricant that forms a soft, ultra thin protective film to prevent corrosion and disperse water. It is for short-term use on critical metal surfaces in avionics, electrical and electronic components. D-5015 NS is safe for use on most paints, plastics and insulation.

APPLICATION

D-5015NS displaces water from electrical and electronic components and provides a thin protective barrier coating that helps prevent corrosion and fungus growth. Excellent for "overnight" tooling protection on highly critical surfaces.

FEATURES

- Safe on most paints, plastics or insulation.
- Light, soft film provides lubrication for moving parts.
- Ideal for in field service use.
- Excellent for electrical and electronic components.

SPECIFICATIONS

- QPL MIL-C-81309E
- Type III Class 2 (aerosol)
- Type III Class 1 (bulk)
- SIKORSKY SS8536
- NSN 8030-00-546-8637

PACKAGING

Aerosol, quarts, gallons, 5 gallons, drums. Special packaging upon request.

Physical Properties

Flash Point:
None

Boiling Range:
-22 to 375 °F.

Vapor Density:
Heavier than air

Specific Gravity (H2O=1):
0.9

Evaporation Rate:
Faster than ether

Material V.O.C.:
514g/l